

```

class cComponent {

    protected $tags = array("input","meter","progress","select","textarea");

    protected $input = array("checkbox","color","date","datetime-local","email",
        "file","month","number","password","radio","range",
        "search","tel","text","time","url","week");

    protected $name;
    protected $value;
    private $type;
    private $default="";
    private $size;
    private $checked="";
    private $maxlength;
    private $options;
    private $required="false";

    private $info;

    protected $place_holder="";

    private $no_label=false;
    private $show_label=false;
    private $label;

    protected $css;

    protected $idd="";

    protected $placeholder="";

    protected $javascript="";
    protected $onClick="";

    protected $events = array();

    function __construct ($n1,$t1,$size,$value,$css,$label)
}

class cBeginDiv extends cComponent {
    function __construct ($name,$css)
    function Show()
}

class cEndDiv extends cComponent {
    function __construct ()
    function Show()
}

class cNewLine extends cComponent {
    function __construct ()
    function Show()
}

class cLabelEx extends cComponent {
    function __construct ($n1,$value)
    function Show()
}

class cEdit extends cComponent {
    function __construct ($n1,$text,$css,$label)
    public function SetText($text)
    public function GetText($text)
    public function Show()
}

```

```

class cNumber extends cComponent {
    function __construct ($n1,$text,$css,$label)
    public function SetText($text)
    public function GetText($text)
    public function Show()
}

class cCheckBox extends cComponent {
    private $ilabel;
    function __construct ($n1,$label,$value)
    function Show()
}

class cRadio extends cComponent {
    public $Items;
    function __construct ($n1,$label,$value)
    public function AddItemEx($item)
    function Show()
}

class cHidden extends cComponent {
    function __construct ($n1,$value)
}

class cSubmit extends cComponent {
    function __construct ($n1,$value,$css)
}

class cButton extends cComponent {
    function __construct ($n1,$value,$css)
}

class cCombobox extends cComponent {
    protected $n1;
    public $Items;
    public $Values;
    private $multiple;
    private $sizet;
    private $label;
    function __construct ($n1,$css,$label)
    function SetMultiple($status)
    public function LoadFromSQL($table,$ident,$label,$clauses)
    public function AddItemEx($label,$codigo)
    public function Show()
}

```

cCustomForm

Main Panel DIV
Class = \$this->css

Title H1 : \$this->title
class name \$this->css

Message Response DIV : blank
Class = message-\$this->css

Controls Background DIV
Name = \$this->idd
Class

Controls
cEdit cSelect cLabelEx
Name: Define in insertion of component

cForm - Create a HTML Form formatted with CSS

```
class cForm extends cCustomForm {
    private $method;
    private $action;
    private $enctype="";
    private $target;
    function __construct ($name,$idd,$method,$action,$enctype,$target)
    public function SetTarget($target)
    public function SetEncType($enctype)
    protected function include_form()
    public function Show()
}
```


cGroup - Create a HTML components group for use with JS (Java Script).

```
class cGroup extends cCustomForm {
    protected $name;
    private $title;
    private $idd;
    function __construct ($name,$idd)
    function SetTitle($title)
    public function SetDivStyle($width,$border,$padding,$other)
    function Show()
}
```



```
class cDialog {
    private $cancel_url;
    private $confirm_url;
    private $text;

    function __construct ($text,$url_cancel,$url_confirm) {

    }

    function show() {

    }
}
```
